

Fig. 1

SIZE ONE  
Fig. 2 INNER CASE  
Fig. 3 OUTER CASE




Fig. 1  
Key Ring





Fig. 2 INNER CASE



SECURING  
PIN HOLES  
1/16" DIAMETER

Fig. 3




Fig. 4




Fig. 5




Fig. 6  
SAFETY LOCK

\* All drawings  
Size  $\times 1/2$

Semi-Automatic Hand Gun  
Size 2 OF 4 SEE 3 OF 7

2057












FIG. 8  
SPRING PIN




FIG. 9  
Springs for lock in safe position  
FIG. 10  
Springs for lock in safe position  
lock in safe position




30F7

KEY & RING INNER CASING OUTER CASING lock core


	$R = \frac{1}{32}$	$R = \frac{1}{32}$	$R = \frac{1}{32}$
SIZE 1	$1" \times \frac{5}{8} \times \frac{1}{16}$	$1" \times \frac{1}{4} \times \frac{1}{16}$	$1" \times \frac{1}{2} \times \frac{1}{32}$
SIZE 2	$\frac{5}{8} " \times \frac{5}{8} " \times \frac{1}{16} R \frac{3}{16}$	$\frac{7}{8} " \times \frac{1}{4} " \times \frac{1}{16} R \frac{2}{16}$	$\frac{7}{8} " \times \frac{1}{2} " \times \frac{1}{32} R \frac{1}{16}$
SIZE 3	$\frac{5}{8} " \times \frac{5}{8} " \times \frac{1}{16} R \frac{5}{16}$	$\frac{5}{8} " \times \frac{1}{4} " \times \frac{1}{16} R \frac{5}{16}$	$\frac{5}{8} " \times \frac{1}{2} " \times \frac{1}{32} R \frac{1}{16}$
SIZE 4	$\frac{1}{2} " \times \frac{5}{8} " \times \frac{1}{16} R \frac{19}{64}$	$\frac{1}{2} " \times \frac{1}{4} " \times \frac{1}{16} R \frac{9}{64}$	$\frac{1}{2} " \times \frac{1}{2} " \times \frac{1}{32} R \frac{5}{16}$

FIG. 12  
Bottom view of spring pin  
Key  
Locking arm  
Locking arm  
Springs  
Locking arm  
Cover  
Ring  
Lock Core  
OPEN



\* R = Diameter

FIG. 13  
Dust  
---> Cover  
---> Spring  
---> Lock Core  
LOCK DUST  
COVER CLOSED  
OPEN












Fig. 10



50F7


100220 = 251362



60F7

四庫全書

lock in safe position



7067

7067-1-123456789

LOCK IN FIRE Position

